

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

C200 Ultrabond, Comp. A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: Sympafix
 Street: Fluorietweg 25e
 Place: NL-1812 RR Alkmaar
 Telephone: +31 1804 68114
 e-mail: office@sympafix.com

1.4. Emergency telephone number:

+49 (0)551-19240 (GIZ-Nord, German und English 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

May cause an allergic skin reaction.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Tetramethylene dimethacrylate;

Methacrylic acid, monoester with propane-1,2-diol;

p-tert-Butylcatechol

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing vapours.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container to an approved waste disposal plant in accordance with local/national regulation.

2.3. Other hazards

No information available.

according to Regulation (EC) No 1907/2006

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 2 of 11

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
2082-81-7	Tetramethylene dimethacrylate			15 - < 30 %
	218-218-1		01-2119967415-30	
	Skin Sens. 1B; H317			
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			< 2,5 %
	248-666-3		01-2119490226-37	
	Eye Irrit. 2, Skin Sens. 1; H319 H317			
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol			< 2,5 %
	254-075-1		01-2119980937-17	
	Acute Tox. 2, Eye Irrit. 2, Aquatic Chronic 3; H300 H319 H412			
98-29-3	p-tert-Butylcatechol			< 1 %
	202-653-9		01-2119548368-28	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1 (M-Factor = 1); H312 H302 H314 H318 H317 H400 H410			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 3 of 11

Extinguishing powder

Water spray jet

Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5 - 25°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 4 of 11

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
2082-81-7	Tetramethylene dimethacrylate			
Worker DNEL, long-term	inhalation	systemic	14,5 mg/m ³	
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	4,3 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
Worker DNEL, long-term	inhalation	systemic	14,7 mg/m ³	
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	8,8 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day	
98-29-3	p-tert-Butylcatechol			
Worker DNEL, long-term	inhalation	systemic	1,6 mg/m ³	

PNEC values

CAS No	Substance	Value
2082-81-7	Tetramethylene dimethacrylate	
Freshwater	0,043 mg/l	
Marine water	0,004 mg/l	
Freshwater sediment	3,12 mg/kg	
Marine sediment	0,312 mg/kg	
Micro-organisms in sewage treatment plants (STP)	2 mg/l	
Soil	0,573 mg/kg	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	
Freshwater	0,904 mg/l	
Marine water	0,904 mg/l	
Freshwater sediment	6,28 mg/kg	
Marine sediment	6,28 mg/kg	
Micro-organisms in sewage treatment plants (STP)	10 mg/l	
Soil	0,727 mg/kg	
98-29-3	p-tert-Butylcatechol	
Freshwater	0,00012 mg/l	
Marine water	0,000012 mg/l	
Freshwater sediment	0,00069 mg/kg	
Marine sediment	0,000069 mg/kg	

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 5 of 11

Additional advice on limit values

This mixture contains quartz filler which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

Eye/face protection

Wear eye/face protection.

Hand protection

Disposable gloves
Recommended material: NBR (Nitrile rubber)
Breakthrough time: > 480 min
Thickness of the glove material: > 0,2 mm
DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid (pasty)	
Colour:	light beige	
Odour:	characteristic	
pH-Value:		not determined

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	not applicable

Flammability

Solid:	not determined
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 6 of 11

Auto-ignition temperature

Solid: not determined
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 1,77 g/cm³

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Response: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2082-81-7	Tetramethylene dimethacrylate				
	oral	LD50 10066 mg/kg	Rat		
	dermal	LD50 > 3000 mg/kg	Rabbit		
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol				
	oral	LD50 > 25 - < 200 mg/kg	Rat		OECD 423
	dermal	LD50 > 2000 mg/kg	Rat		
98-29-3	p-tert-Butylcatechol				
	oral	LD50 815 mg/kg	Rat		
	dermal	LD50 1331 mg/kg	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Tetramethylene dimethacrylate; Methacrylic acid, monoester with propane-1,2-diol; p-tert-Butylcatechol)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
2082-81-7	Tetramethylene dimethacrylate					
	Acute algae toxicity	ErC50 mg/l	9,79	72 h		
	Crustacea toxicity	NOEC mg/l	5,09	21 d		
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol					
	Acute algae toxicity	ErC50 mg/l	> 97,2	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	> 143	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC mg/l				
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol					
	Acute fish toxicity	LC50 mg/l	17 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50 mg/l	245 mg/l	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	28,8	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC mg/l	57,8	72 d	Desmodesmus subspicatus	OECD 201
98-29-3	p-tert-Butylcatechol					
	Acute fish toxicity	LC50 mg/l	0,12	96 h	Brachydanio rerio (zebra-fish)	OECD 203
	Acute algae toxicity	ErC50 mg/l	10,17	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50 mg/l	0,48	48 h	Daphnia magna (Big water flea)	OECD 202
	Crustacea toxicity	NOEC mg/l	0,135	21 d	Daphnia magna (Big water flea)	OECD 211
	Acute bacteria toxicity	(16 mg/l)		3 h		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
2082-81-7	Tetramethylene dimethacrylate			
	OECD 310	84 %	28	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
	OECD 301C	81%	28	
98-29-3	p-tert-Butylcatechol			
	OECD 302B	70,73 %	28	

12.3. Bioaccumulative potential

The product has not been tested.

according to Regulation (EC) No 1907/2006

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 9 of 11

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2082-81-7	Tetramethylene dimethacrylate	3,1
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	0,97
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol	2,1
98-29-3	p-tert-Butylcatechol	1,98

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations.

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 10 of 11

Inland waterways transport (ADN)

- | | |
|--|--|
| 14.1. UN number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Marine transport (IMDG)

- | | |
|--|--|
| 14.1. UN number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Air transport (ICAO-TI/IATA-DGR)

- | | |
|--|--|
| 14.1. UN number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)
(SEVESO III):

Additional information

VOC content: 0,7 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

- | | |
|--------------------------------|--|
| Employment restrictions: | Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). |
| Water hazard class (D): | 1 - slightly hazardous to water |
| Skin resorption/Sensitization: | Causes allergic hypersensitivity reactions. |

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,8,15.

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation
(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS: Chemical Abstracts Service

according to Regulation (EC) No 1907/2006

C200 Ultrabond, Comp. A

Revision date: 07.08.2020

Page 11 of 11

CLP: Classification, Labeling and Packaging
 DMEL: Derived Minimal Effect level
 DNEL: Derived No Effect Level
 EC50: Effective concentration, 50%
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)
 ICAO: International Civil Aviation Organization
 IC50: Inhibitory concentration, 50%
 IMDG: International Maritime Code for Dangerous Goods
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 NOEC: No Observed Effect Concentration
 OECD: Organisation for Economic Co-operation and Development
 PBT: persistent, bioaccumulative and toxic
 vPvB: very persistent and very bioaccumulative
 PNEC: Predicted No Effect Concentration
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)
 VOC: Volatile organic compound
 Acute Tox. 2: Acute toxicity, Category 2
 Acute Tox. 3: Acute toxicity, Category 3
 Acute Tox. 4: Acute toxicity, Category 4
 Aquatic Chronic 1: Long-term aquatic hazard, Category 1
 Aquatic Chronic 3: Long-term aquatic hazard, Category 3
 Eye Dam. 1: Serious eye damage/eye irritation, Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2
 Skin Corr. 1B: Skin corrosion/irritation, Category 1B
 Skin Sens. 1: Skin sensitization, Category 1
 Skin Sens. 1B: Skin sensitization, Category 1B

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H300 Fatal if swallowed.
 H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

C200 Ultrabond, Comp. B

Revision date: 07.08.2020

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

C200 Ultrabond, Comp. B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: Sympafix
Street: Fluorietweg 25e
Place: NL-1812 RR Alkmaar
Telephone: +31 1804 68114
e-mail: office@sympafix.com

1.4. Emergency telephone number:

+49 (0)551-19240 (GIZ-Nord, German und English 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

May cause an allergic skin reaction.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Dibenzoyl peroxide

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing vapours.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container to an approved waste disposal plant in accordance with local/national regulation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

C200 Ultrabond, Comp. B

Revision date: 07.08.2020

Page 2 of 10

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
94-36-0	Dibenzoyl peroxide			5 - < 10 %
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1 (M-Factor = 10); H241 H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Further Information

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam
Extinguishing powder
Water spray jet
Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic
Carbon monoxide

C200 Ultrabond, Comp. B

Revision date: 07.08.2020

Page 3 of 10

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand
Treat the recovered material as prescribed in the section on waste disposal.
Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.
Wear personal protection equipment (refer to section 8).
Avoid contact with skin, eyes and clothes.
When using do not eat, drink or smoke.
Wash hands thoroughly after handling.
Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong
Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5 - 25°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

C200 Ultrabond, Comp. B

Revision date: 07.08.2020

Page 4 of 10

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

DNEL/DNEL values

CAS No	Substance	Exposure route	Effect	Value
94-36-0	Dibenzoyl peroxide			
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	13,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	39 mg/m ³

PNEC values

CAS No	Substance	Value
94-36-0	Dibenzoyl peroxide	
Freshwater		0,00002 mg/l
Marine water		0,000002 mg/l
Freshwater sediment		0,013 mg/kg
Marine sediment		0,001 mg/kg

Additional advice on limit values

This mixture contains quartz filler which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

Eye/face protection

Wear eye/face protection.

Hand protection

Disposable gloves
Recommended material: NBR (Nitrile rubber)
Breakthrough time: > 480 min
Thickness of the glove material: > 0,2 mm
DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective

C200 Ultrabond, Comp. B

Revision date: 07.08.2020

Page 5 of 10

gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid (pasty)	
Colour:	black	
Odour:	characteristic	
pH-Value:		not determined

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	not applicable

Flammability

Solid:	not determined
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

Auto-ignition temperature

Solid:	not determined
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidising.	
Vapour pressure:	not determined
Density:	1,77 g/cm ³
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined	
Partition coefficient:	not determined
Vapour density:	not determined
Evaporation rate:	not determined

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

see section 10.3

10.2. Chemical stability

according to Regulation (EC) No 1907/2006

C200 Ultrabond, Comp. B

Revision date: 07.08.2020

Page 6 of 10

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

Benzoic acid

Benzene

Biphenyl

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
94-36-0	Dibenzoyl peroxide				
	oral	LD50 > 5000 mg/kg	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Dibenzoyl peroxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus)

IC10: (0 - 72h) = 60 mg/l

IC50: (0 - 72h) = > 500 mg/l

OECD 202 (Daphnia magna (Big water flea))

EC0/NOEC (48h) = 100 mg/l

EC50 (48h) = > 500 mg/l

EC100 (48h) = >> 500 mg/l

according to Regulation (EC) No 1907/2006

C200 Ultrabond, Comp. B

Revision date: 07.08.2020

Page 7 of 10

OECD 203 (Brachydanio rerio (zebra-fish))

LC0/NOEC = 500 mg/l

LC50 = > 500 mg/l

LC100 = >>500 mg/l

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
94-36-0	Dibenzoyl peroxide					
	Acute fish toxicity	LC50 mg/l	0,0602	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50 mg/l	0,0711	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50	0,11 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202
	Algae toxicity	NOEC mg/l	0,02	3 d	Pseudokirchneriella subcapitata	OECD 201
	Crustacea toxicity	NOEC mg/l	0,001	21 d	Daphnia magna (Big water flea)	OECD 211
	Acute bacteria toxicity	(35 mg/l)	0,5 h			OECD 209

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations.

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

C200 Ultrabond, Comp. B

Revision date: 07.08.2020

Page 8 of 10

List of Wastes Code - residues/unused products

- 080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

- 080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

- 150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

- | | |
|---|--|
| <u>14.1. UN number:</u> | No dangerous good in sense of this transport regulation. |
| <u>14.2. UN proper shipping name:</u> | No dangerous good in sense of this transport regulation. |
| <u>14.3. Transport hazard class(es):</u> | No dangerous good in sense of this transport regulation. |
| <u>14.4. Packing group:</u> | No dangerous good in sense of this transport regulation. |

Inland waterways transport (ADN)

- | | |
|---|--|
| <u>14.1. UN number:</u> | No dangerous good in sense of this transport regulation. |
| <u>14.2. UN proper shipping name:</u> | No dangerous good in sense of this transport regulation. |
| <u>14.3. Transport hazard class(es):</u> | No dangerous good in sense of this transport regulation. |
| <u>14.4. Packing group:</u> | No dangerous good in sense of this transport regulation. |

Marine transport (IMDG)

- | | |
|---|--|
| <u>14.1. UN number:</u> | No dangerous good in sense of this transport regulation. |
| <u>14.2. UN proper shipping name:</u> | No dangerous good in sense of this transport regulation. |
| <u>14.3. Transport hazard class(es):</u> | No dangerous good in sense of this transport regulation. |
| <u>14.4. Packing group:</u> | No dangerous good in sense of this transport regulation. |

Air transport (ICAO-TI/IATA-DGR)

- | | |
|---|--|
| <u>14.1. UN number:</u> | No dangerous good in sense of this transport regulation. |
| <u>14.2. UN proper shipping name:</u> | No dangerous good in sense of this transport regulation. |
| <u>14.3. Transport hazard class(es):</u> | No dangerous good in sense of this transport regulation. |
| <u>14.4. Packing group:</u> | No dangerous good in sense of this transport regulation. |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

C200 Ultrabond, Comp. B

Revision date: 07.08.2020

Page 9 of 10

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)
(SEVESO III):

Additional information

VOC content: 0,9 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3.

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation
(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS: Chemical Abstracts Service
CLP: Classification, Labeling and Packaging
DMEL: Derived Minimal Effect level
DNEL: Derived No Effect Level
EC50: Effective concentration, 50%
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)
ICAO: International Civil Aviation Organization
IC50: Inhibitory concentration, 50%
IMDG: International Maritime Code for Dangerous Goods
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
NOEC: No Observed Effect Concentration
OECD: Organisation for Economic Co-operation and Development
PBT: persistent, bioaccumulative and toxic
vPvB: very persistent and very bioaccumulative
PNEC: Predicted No Effect Concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)
VOC: Volatile organic compound
Aquatic Chronic 3: Long-term aquatic hazard, Category 3
Acute Tox. 2: Acute toxicity, Category 2
Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

C200 Ultrabond, Comp. B

Revision date: 07.08.2020

Page 10 of 10

Skin Sens. 1: Skin sensitization, Category 1

STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)